

CERTIFICATE OF COMPLIANCE

Certificate Number 20151204-E241282
Report Reference E241282-20111114
Issue Date 2015-DECEMBER-04

Issued to: ARMACELL GMBH
ROBERT-BOSCH-STRASSE 10
48153 MUENSTER GERMANY

**This is to certify that
representative samples of** COMPONENT - PLASTICS
USR/CNR :
Ethylene Propylene Diene Terpolymer (EPDM) : Armaflex
HT
Nitrile Rubber (NBR) : AF/Armaflex (b), AF/Armaflex UL1,
AF/Armaflex UL2 (c), NH/Armaflex (d)

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: For standard information please visit UL iQ Plastics
Database
(<https://my.secure.home1.ul.com/portal/page/portal/usa/iQ/iQWelcome>)

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance
capabilities and are intended for use as components of complete equipment submitted for investigation rather
than for direct separate installation in the field. The final acceptance of the component is dependent upon its
installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20151204-E241282
Report Reference E241282-20111114
Issue Date 2015-DECEMBER-04

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

INDEX TO FOOTNOTES:

- (a) - Density range: 0.070-0.110 g/cc.
- (b) - Density Range 0.040 - 0.080 g/cc
- (c) - Density Range 0.066 - 0.081 g/cc
- (d) - Density Range 0.055 - 0.085 g/cc



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

