



product description: it is used to divide the interior of the trunkings, thus allowing a better manipulation with the inserted cables and clarity
 possibility to install in places with risk of flammable gases and vapor – danger zone 2
 possibility to install in places with explosive risk of dust – danger zone 22

item number: PEKE 60_-C

material: PVC - Pb-free

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

color: white

length: 2 m

length tolerance: ±10 mm

package: 2 m / 20 m / 160 m

weight: 0,12 kg/m

certification: EN 50085-1 ed.2:06, EN 50085-2-1:07

storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: acetone, benzen, chlorinated hydrocarbons, tetrachlorocarbon

compatible with:

- EKE 60X60
- EKE 100X60
- EKE 140X60
- EKE 180X60
- PK 110X70 D
- PK 140X70 D
- PK 170X70 D
- PK 90X55 D
- PK 120X55 D
- PK 160X65 D
- PK 210X70 D
- PK 110X65 D
- PK 130X65 D