

Floodlight

Specifications - PILA BVP008 4000k

Benefits

- ▶ Energy saving
- ▶ Robust luminaire
- ▶ Reliable quality



Product description	PILA BVP008 10W 4000k	PILA BVP008 20W 4000k	PILA BVP008 30W 4000k	PILA BVP008 50W 4000k
Light output (lm)	950	1900	2850	4750
Power (W)	10	20	30	50
CCT (K)	4000	4000	4000	4000
Mains voltage	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz
Lifetime	35,000 hrs	35,000 hrs	35,000 hrs	35,000 hrs
CRI	80	80	80	80
Connection	Flying wire	Flying wire	Flying wire	Flying wire
IP rating	IP65 / IK06	IP65 / IK06	IP65 / IK06	IP65 / IK06
Power factor	> 0.9	> 0.9	> 0.9	> 0.9
Safety class	Class I	Class I	Class I	Class I
Housing material	Glass/Aluminium	Glass/Aluminium	Glass/Aluminium	Glass/Aluminium
Color	Dark grey	Dark grey	Dark grey	Dark grey
EOC	871951453298499	871951453297799	871951453296099	871951453295399
12NC	9114 018 20583	9114 018 21583	9114 018 23583	9114 018 24583