


Technical data sheet

0° socket, with earthing pin, encoded version, triple

Item no. 6120316



Socket with earthing pin, triple 0°, encoded version, with increased touch protection, with screwless terminals, 2-pin, 16 A, 250 V~, with connection terminals according to IEC 60884-1. The socket can only be used in connection with an encoding pin of type CST-STD.

PC Polycarbonate


Additional product text 1
Additional product text 2

Note: The encoding pin is not contained in the scope of supply.
For installation in Rapid 45 trunking, device installation trunking, service poles, underfloor systems and desk boxes.

Master data

Item no.	6120316
Type	STD-F0K SR03
Description 1	Socket 0°, triple, coded
Description 2	with earth pin
Dimension	250V, 10/16A
Colour	Signal red
RAL number	3001
Material	Polycarbonate
Material symbol	PC
Smallest sales unit (VG)	1,00 Piece
Weight	11,80 kg/100 pc.

Technical data



Width	135,00 mm
Height	45,00 mm
Depth	39,00 mm
Cover	Central plate
Closable	☐
Connection type	Screwless terminal
Printed label/coding	Without printing
Version	triple 0°
Version	Socket 0°, triple, coded, with earth pin
Surface version	Matt
Sockets/switch version	Protective contact pin
Version for	Protective contact pin
Number of poles	2,00
Number of units	3,00
Number of modules (for modular construction)	0,00
Number of switchable sockets	0,00
Ejection mechanism	☐

Technical data sheet

0° socket, with earthing pin, encoded version, triple

Item no. 6120316



Technical data

Fastening type	Lock
Labelling panel	☐
Operating temperature	-5,00 - 40,00 °C
Error current protection	☐
For more difficult conditions (according to VDE)	☐
Halogen-free	☒
Insulated installation	☐
Increased touch protection	☒
Hinged cover	☐
Coding	Yes
Warning light	☐
With on/off switch	☐
With fine-wire fuse	☐
With functional lighting	☐
With orientation lighting	☐
Mounting type	Device installation duct
Nominal voltage	250,00 V
Nominal current	16,00 A
Protection rating	Other
Special power supply	Without special power supply
Socket version	NF
Socket angle	0°
Transparent	☐
Surge protection	☐
Rotated central insert	☐