

PRODUCT DATASHEET

URBAN LITE L 100W 865 IP65 GY

URBAN LITE | Road, path and area lighting



Areas of application

- Streets
- Parking lots, city squares, parks

Product benefits

- Lightweight design
- Slim profile
- 3 years guarantee

Product features

- Asymmetric light distribution for various application areas
- Side-entry mounting for 48...60 mm poles
- Integrated 220...240 V_{AC} driver

TECHNICAL DATA

Electrical data


Nominal wattage	100.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	440 mA
Max. no. of lum. on circuit break. C16 A	29
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	10500 lm
Luminous efficacy	105 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	140 ° x 95 °

Dimensions & Weight

Length	455.00 mm
Width	170.00 mm
Height	53.00 mm
Product weight	1120.00 g
Cable length	400 mm



Materials & Colors

Product color	Gray
---------------	------

Housing color	Gray
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+35 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Side entry
Mounting location	Pole
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	35000 h
Number of switching cycles	20000

Certificates & Standards

Standards	CE / REACH / RoHS
Luminaire with limited surface temperature, "D sign"	No

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075678194	Folding box 1	58 mm x 490 mm x 195 mm	1374.00 g	5.54 dm ³
4058075678200	Shipping box 8	500 mm x 400 mm x 252 mm	11883.00 g	50.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.